

Alan Brading
 Mobile: 021 433 038
 www.supascoota.co.nz



COMBI 18

Specifications	COMBI 18
Drive Wheels size	200 mm (8 inch)
Caster Wheels size	178 mm (7 inch)
Overall Length	1180 mm (46.5 inch)
★ Overall Width	580 mm (22.8 inch)
Overall Height	1010 mm (39.8 inch)
Standard Seat Width	450 mm (17.7 inch)
Standard Seat Depth	450 mm (17.7 inch)
Back rest height	470 mm (18.5 inch)
Weight Capacity	150 Kg (330 lbs)
★ Total Weight With Batteries (SLA)	37.3 kg (82 lbs)
Weight of Motor mount complete	14.9 Kg (32.8 lbs)
Heaviest Piece	14.9 Kg (32.8 lbs)
Breaks Down Into	6 pieces
Maximum Speed SLA battery	6.5 kph (4.0 mph)
Turning Radius	900 mm (35.4 inch)
Ground Clearance	83 mm (3.3 inch)
Battery (SLA/Lithium)	24V 15ah
Weight of battery (SLA/Lithium)	9.2 Kg / 4 Kg (20 lbs / 9 lbs)
Slope Grade Ability	9 degree
Travel Distance SLA/Lithium	Up to 10 / 16.5km (6.2 / 10.2mile)
Battery Charger SLA	2A Off Board
Battery Charger Lithium	4A Off Board
Armrest height	160 / 215 mm (6.3 / 8.5 inch)
Brake	Dynamic Braking and Electromagnetic Brake

COMBI 20

Specifications	COMBI 20
Drive Wheels size	200 mm (8 inch)
Caster Wheels size	178 mm (7 inch)
Overall Length	1180 mm (46.5 inch)
Overall Width	620 mm (25.2 inch)
Overall Height	1010 mm (39.8 inch)
Standard Seat Width	490 mm (19.3 inch)
Standard Seat Depth	450 mm (17.7 inch)
Back rest height	470 mm (18.5 inch)
Weight Capacity	150 Kg (330 lbs)
Total Weight With Batteries (SLA)	37.7 kg (83 lbs)
Weight of Motor mount complete	15 Kg (33 lbs)
Heaviest Piece	15 Kg (33 lbs)
Breaks Down Into	6 pieces
Maximum Speed SLA battery	6.5 kph (4.0 mph)
Turning Radius	1100 mm (43.3 inch)
Ground Clearance	83 mm (3.3 inch)
Battery (SLA/Lithium)	24V 15ah
Weight of battery (SLA/Lithium)	9.2 Kg / 4 Kg (20 lbs / 9 lbs)
Slope Grade Ability	9 degree
Travel Distance SLA/Lithium	Up to 10 / 16.5km (6.2 / 10.2mile)
Battery Charger SLA	2A Off Board
Battery Charger Lithium	4A Off Board
Armrest height	160 / 215 mm (6.3 / 8.5 inch)
Brake	Dynamic Braking and Electromagnetic Brake

COMBI 18SP

Specifications	COMBI 18SP
Drive Wheels size	260 mm (10 inch)
Caster Wheels size	200 mm (8 inch)
Overall Length	1180 mm (46.5 inch)
Overall Width	580 mm (22.8 inch)
Overall Height	1010 mm (39.8 inch)
Standard Seat Width	450 mm (17.7 inch)
Standard Seat Depth	450 mm (17.7 inch)
Back rest height	470 mm (18.5 inch)
Weight Capacity	125 Kg (275 lbs)
Total Weight With Batteries (SLA)	39.7 kg (87 lbs)
Weight of Motor mount complete	17.3 Kg (38 lbs)
Heaviest Piece	17.3 Kg (38 lbs)
Breaks Down Into	6 pieces
Maximum Speed SLA battery	9 kph (5.6 mph)
Turning Radius	900 mm (35.4 inch)
Ground Clearance	83 mm (3.3 inch)
Battery (SLA/Lithium)	24V 15ah
Weight of battery (SLA/Lithium)	9.2 Kg / 4 Kg (20 lbs / 9 lbs)
Slope Grade Ability	8 degree
Travel Distance SLA/Lithium	Up to 10 / 16.5km (6.2 / 10.2mile)
Battery Charger SLA	2A Off Board
Battery Charger Lithium	4A Off Board
Armrest height	160 / 215 mm (6.3 / 8.5 inch)
Brake	Dynamic Braking and Electromagnetic Brake

COMBI 20SP

Specifications	COMBI 20SP
Drive Wheels size	260 mm (10 inch)
Caster Wheels size	200 mm (8 inch)
Overall Length	1180 mm (46.5 inch)
Overall Width	620 mm (25.2 inch)
Overall Height	1010 mm (39.8 inch)
Standard Seat Width	490 mm (19.3 inch)
Standard Seat Depth	450 mm (17.7 inch)
Back rest height	470 mm (18.5 inch)
Weight Capacity	125 Kg (275 lbs)
Total Weight With Batteries (SLA)	39.8 kg (87.5 lbs)
Weight of Motor mount complete	17.4 Kg (38.2 lbs)
Heaviest Piece	17.4 Kg (38.2 lbs)
Breaks Down Into	6 pieces
Maximum Speed SLA battery	9 kph (5.6 mph)
Turning Radius	1100 mm (43.3 inch)
Ground Clearance	83 mm (3.3 inch)
Battery (SLA/Lithium)	24V 15ah
Weight of battery (SLA/Lithium)	9.2 Kg / 4 Kg (20 lbs / 9 lbs)
Slope Grade Ability	8 degree
Travel Distance SLA/Lithium	Up to 10 / 16.5km (6.2 / 10.2mile)
Battery Charger SLA	2A Off Board
Battery Charger Lithium	4A Off Board
Armrest height	160 / 215 mm (6.3 / 8.5 inch)
Brake	Dynamic Braking and Electromagnetic Brake

★ Excluded self-propelled wheels